



| 技术要求 (Technical Specifications) : | |
|-------------------------------------|---------------------------|
| 额定电流 (Current Rating) | 2A |
| 额定电阻 (Rated Resistance) | 100 milliohm max |
| 满行程 (Full Stroke) | 1.70mm |
| 额定行程 (Rated Stroke) | 1.10mm |
| 额定弹力 (Spring Force) | 45±9gf@load 1.10mm(1.6oz) |
| 频率带宽 (Bandwidth) | -1dB@10.3GHZ |
| 测试寿命 (Mechanical Life Exceeds) | 100000 cycles |

| Plunger(I) | |
|------------|------|
| U(1) | F(1) |
| B(1) | J(1) |

| Plunger(II) | |
|-------------|------|
| U(2) | F(2) |
| B(2) | J(2) |

| 材质 (Materials) : | |
|------------------|------------------------|
| 针头 (Plunger) | BeCu,gold-plated |
| 针管 (Barrel) | Ph,gold-plated |
| 弹簧 (Spring) | SWP or SUS,gold-plated |

| 成品型号 (Product Type) : | |
|---|--|
| HDE065-XX-113-1.6GG(BB) <small>系列 规格 头型 总长 弹力 镀金 针头材质</small> 订购举例:HDE065-JB-113-1.6GG(BB) | |